



NTK BEARING PRECISION AXLE CORP.

32 mm x 58 mm x 13 mm NTN 60/32ZZ deep groove ball bearings



60/32ZZ Bearing 2D drawings and 3D CAD models

Bearing No. 60/32ZZ

Size	32x58x13 mm
Bore Diameter	32 mm
Outer Diameter	58 mm
Width	13 mm
d	32 mm
D	58 mm
B	13 mm
C	13 mm
rn	0,5 mm
r min.	1 mm
da min.	37 mm
da max	39 mm
Da max.	53 mm
ra max.	1 mm
Weight	0,129 Kg
Basic dynamic load rating (C)	11,8 kN
Basic static load rating (C0)	8,05 kN
(Grease) Lubrication Speed	12 000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.133
Product Group	B00308
Enclosure	2 Metal Shields



NTK BEARING PRECISION AXLE CORP.

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	32MM Bore; 58MM Outside Diameter; 13MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	60/32ZZ/2A
Weight / LBS	0.042
Bore	1.26 Inch 32 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Outside Diameter	2.283 Inch 58 Millimeter
bore diameter:	32 mm
precision rating:	ISO Class 0
outside diameter:	58 mm
finish/coating:	Uncoated
overall width:	13 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round



NTK BEARING PRECISION AXLE CORP.

cage material:	Steel
closure type:	Double Shielded
inner ring width:	13 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	13 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	12000 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	15000 RPM
dynamic load capacity:	11800 N
series:	60
static load capacity:	8050 N
manufacturer product page:	Click here